

by[®]
bjorn

Manual

Lava Paint

Matte textured paint with mineral appearance



What is Lava Paint?

Lava Paint by By Bjorn is a high-quality matte textured paint with a subtle mineral appearance. With two coats you create a calm, cloudy effect that adds warmth and character to any space.



Who is it suitable for?

Lava Paint is suitable for everyone.

You don't need to be a professional. With the right preparation and application technique, Lava Paint is easy to apply yourself.

Where can you apply Lava Paint?

Lava Paint is suitable for:

- Walls and ceilings
- Furniture, doors and cabinets
- Indoors and outdoors
- Both new builds and existing homes

Surface and preparation

The surface must be:

- Flat
- Dry
- Dust- and grease-free
- Sound and stable

Plastered or highly absorbent surface?

Use By Bjorn Primer first.

Wall covering or existing paint layer?

Directly applicable, provided it is clean and firm.

How to Apply Lava Paint in 2 Coats

With the right preparation, Lava Paint is easy to apply. Work calmly for the best result.

1

Preparation



Make sure the surface is flat, clean, dry and dust-free. Lightly sand the wall for a smooth and even result. Remove loose parts and fill any damage. For absorbent surfaces, such as plastered walls, use By Bjorn Primer first.

2

Apply first coat



Dilute the Lava Paint with 10% water and stir the mixture well. Pour the paint into a paint tray and apply the first coat with a By Bjorn block brush. Work crosswise (horizontally and vertically) and distribute the product evenly. Do not apply too thickly.

3

Apply second coat



Let the first coat dry for approximately 2-6 hours. Then apply the second coat crosswise again. This creates the characteristic cloudy texture effect. If no protective coating is required, your Lava Paint finish is complete once the second coat has dried.

4

Extra protection (optional)



For areas that require extra protection or easier cleaning, such as bathrooms or toilets, finish the wall with By Bjorn Coating. Let the wall dry for 12 hours first. Then lightly sand with 220 grit and apply a coat of By Bjorn Coating with a felt roller.

Practical information

Coverage

Coverage: approximately 3.5 m² per kilo for two coats, with 10% water dilution.

* The stated coverage is a guideline. Actual coverage may vary depending on absorption, surface texture and application method.

Drying time

Dust dry after approximately 2 hours.
Recoat after approximately 2–6 hours.
Fully cured after approximately 48 hours.

Application

Only apply Lava Paint at a minimum temperature of 10°C.
Avoid application in direct sunlight and ensure adequate ventilation.

Maintenance

Once fully dry, the wall can be cleaned normally with a soft cloth. Do not use aggressive or abrasive cleaning agents.

Shelf life

Minimum 12 months shelf life in original, unopened packaging.
Store in a cool, dry and frost-free place.

Technical properties

Sheen level: Matte
Dilution: Water (max. 20%)
* By Bjorn recommendation: dilute with 10% water.
Tool cleaning: Water

Have any doubts or questions during application?

We are happy to help. Find more information at bybjorn.nl, email us or feel free to call us at 0541-551000

Thank you for trusting By Bjorn.